


Product information

FBRBSAA Flexible Rubber Bellows



No.	Name	Material
1	Outer / Inner Rubber	NBR
2	Key Frame	Nylon, Fabric
3	Pressured Ring	Steel
4	Flange	Steel, Plated

Type			
Working Pressure, BAR	16	Burst Pressure, BAR	48
Vacuum %	65		
Applicable Temperature	115°C		
Applicable Medias	Air, compressed air, water, sea water, hot water, oil, acid, alkali and so on.		
Flange Dimensions	ANSI B16.5		

Nominal Diameter mm	Length (mm) L	Axial Displacement		Horizontal Displacement (mm)	Deflexion Angle (a, +a)	Flange	
		Extension (mm)	Compression (mm)			PCD mm	Bolt Size inch
50	105	7	10	10	15°	120.6	4 x 5/8
65	115	7	13	11	15°	139.7	4 x 5/8
80	135	8	15	12	15°	152.4	4 x 5/8
100	150	10	19	13	15°	190.5	8 x 5/8
125	165	12	19	13	15°	215.9	8 x 3/4
150	180	12	20	14	15°	241.3	8 x 3/4
200	210	16	25	22	15°	298.4	8 x 3/4
250	230	16	25	22	15°	361.9	12 x 7/8
300	245	16	25	22	15°	431.8	12 x 7/8