


Product information

FBRESE Flexible Rubber Bellows



No.	Name	Material
1	Outer / Inner Rubber	EPDM
2	Key Frame	Nylon, Fabric
3	Pressured Ring	Steel
4	Flange	Steel, Plated

Type			
Working Pressure, BAR	16	Burst Pressure, BAR	48
Vacuum %	65		
Applicable Temperature	115°C		
Applicable Medias	Air, compressed air, water, sea water, hot water, oil, acid, alkali and so on.		
Flange Dimensions	AS2129 Table E		

Nominal Diameter mm	Length (mm) L	Axial Displacement		Horizontal Displacement (mm)	Deflexion Angle (a, +a)	Flange	
		Extension (mm)	Compression (mm)			PCD mm	Bolt Size mm
32	95	6	9	9	15°	87	4 x 12
40	95	6	10	9	15°	98	4 x 12
50	105	7	10	10	15°	114	4 x 16
65	115	7	13	11	15°	127	4 x 16
80	135	8	15	12	15°	146	4 x 16
100	150	10	19	13	15°	178	8 x 16
125	170	12	19	13	15°	210	8 x 16
150	180	12	20	14	15°	235	8 x 20
200	210	16	25	22	15°	292	8 x 20
250	240	16	25	22	15°	356	12 x 20
300	260	16	25	22	15°	406	12 x 24
350	265	16	25	22	15°	470	12 x 24
400	265	16	25	22	15°	521	12 x 24
450	265	16	25	22	15°	584	16 x 24
500	265	16	25	22	15°	641	16 x 24
600	265	16	25	22	15°	756	16 x 30
700	265	16	25	22	15°	845	20 x 30
800	265	16	25	22	15°	984	20 x 30
900	265	16	25	22	15°	1092	24 x 33
1000	265	18	26	24	15°	1175	24 x 36
1200	265	18	26	24	15°	1410	32 x 36