

Gauges

Stainless Steel Casing, Glycerine Filled



Case: Stainless Steel
Window: Polycarbonate
Bourbon Tube: Copper Alloy
Movement: Copper Alloy
Temperature: -20°C to +60 °C
Threads: BSPT, ISO 7/1

Range		Face	50		65		100
KPA	PSI	Thread	1/4" BSPT		1/4" BSPT		3/8" BSPT
			Bottom Entry	Rear Entry	Bottom Entry	Rear Entry	Bottom Entry
0-100	0-15				GHP063LP2-0100	GHP063CP2-0100	
0-250	0-35		GHP050LP2-0250	GHP050CP2-0250	GHP063LP2-0250	GHP063CP2-0250	GHP100LP3-0250
0-400	0-55		GHP050LP2-0400	GHP050CP2-0400	GHP063LP2-0400		GHP100LP3-0400
0-600	0-85		GHP050LP2-0600	GHP050CP2-0600	GHP063LP2-0600	GHP063CP2-0600	
0-800	0-115		GHP050LP2-0800	GHP050CP2-0800	GHP063LP2-0800	GHP063CP2-0800	GHP100LP3-0800
0-1000	0-145		GHP050LP2-1000	GHP050CP2-1000	GHP063LP2-1000	GHP063CP2-1000	GHP100LP3-1000
0-1600	0-230		GHP050LP2-1600	GHP050CP2-1600	GHP063LP2-1600	GHP063CP2-1600	GHP100LP3-1600
0-2500	0-350				GHP063LP2-2500	GHP063CP2-2500	GHP100LP3-2500
0-4000	0-600				GHP063LP2-4000	GHP063CP2-4000	GHP100LP3-4000
0-6000	0-870				GHP063LP2-6000	GHP063CP2-6000	
0-8000	0-1150				GHP063LP2-8000	GHP063CP2-8000	
0-10000	0-1500				GHP063LP2-10000		
0-16000	0-2320				GHP063LP2-16000	GHP063CP2-16000	
0-25000	0-3600				GHP063LP2-25000	GHP063CP2-25000	

Compound

-100 to + 150 Kpa			GHC063LP2-0150	GHC063CP2-0150	
-------------------	--	--	----------------	----------------	--

Black Steel, Dry



Case: Steel, Black
Window: Acrylic
Bourbon Tube: Copper Alloy
Movement: Brass
Temperature: -20°C to +60 °C
Threads: BSPT, ISO 7/1

Range		Face	50		65		100
KPA	PSI	Thread	1/4" BSPT		1/4" BSPT		3/8" BSPT
			Bottom Entry	Rear Entry	Bottom Entry	Rear Entry	Bottom Entry
0-100	0-15						
0-250	0-35						
0-400	0-55						GHP100LP3-0400
0-600	0-85					GHP063BDLP2-0600	
0-800	0-115		GHP050BDLP2-0800		GHP063BDLP2-0800		GHP100LP3-0800
0-1000	0-145		GHP050BDLP2-1000	GHP063BDLP2-1000	GHP063BDLP2-1000	GHP063BDLP2-1000	GHP100LP3-1000
0-1600	0-230		GHP050BDLP2-1600	GHP063BDLP2-1600	GHP063BDLP2-1600	GHP063BDLP2-1600	GHP100LP3-1600
0-2500	0-350						GHP100LP3-2500
0-4000	0-600				GHP063BDLP2-4000	GHP063BDLP2-4000	
0-6000	0-870				GHP063BDLP2-6000	GHP063BDLP2-6000	
0-8000	0-1150						
0-10000	0-1500						
0-16000	0-2320						
0-25000	0-3600						

Compound

-100 to + 150 Kpa			GHC063BDLP2-0150		GHC100BDLP3-0150
-------------------	--	--	------------------	--	------------------