

SKU: 125.85.402.104

Capacity: 30 m of 3/8" Hose

Perf: 5,000 PSI (Max.)

In/Out:

Features

- Heavy Duty A-Frame Crank Reel
- A Frame style provides more support in mobile applications
- Universal 130 mm hole centre footprint
- High gloss powder-coated finish
- Extra heavy duty 6 point locking pin and adjustable rubber friction brake
- Dual heavy-duty sealed axle ball bearing with stainless steel hardware
- High-flow stainless steel swivel with Parker Viton O-Rings
- The reversible handle and swivel, let you switch sides for the best mounting option
- Hose guide to guard hose from reload damage (2100462)
- Optional 12-Volt power rewind kit. Includes mounting bracket, ring gear and hardware (103166)
- **HOSE NOT INCLUDED**

Specifications

- **Capacity:** 30 m of 3/8" Hose
 - **Max Pressure:** 5,000 PSI
 - **Inlet Hose:**
 - **Outlet Swivel:**
 - **Material:** Stainless Steel
 - **Dimensions:** W 30 cm x H 43 cm x D 36 cm
 - **Weight:** 5 kg
-



Recommended Accessories

- **1/2" BSPT - Suits BAR Reel** 222 2103180
- **Hose Reel Guide (C01)** 222 2100462
- **Swivel - Hose Reel (C)** 165 43.917X

