

SKU: 125.85.402.105

Capacity: 45 m of 3/8" Hose
Perf: 5,000 PSI (Max.)
In/Out: 1/2" F NPT

Features

- Heavy Duty A-Frame Crank Reel
- A Frame style provides more support in mobile applications
- Universal 130 mm hole centre footprint
- High gloss powder-coated finish
- Extra heavy duty 6 point locking pin and adjustable rubber friction brake
- Dual heavy-duty sealed axle ball bearing with stainless steel hardware
- High-flow stainless steel swivel with Parker Viton O-Rings
- The reversible handle and swivel, let you switch sides for the best mounting option
- Hose guide to guard hose from reload damage (2100462)
- Optional 12-Volt power rewind kit. Includes mounting bracket, ring gear and hardware (103166)
- **HOSE NOT INCLUDED**

Specifications

- **Capacity:** 45 m of 3/8" Hose
- **Max Pressure:** 5,000 PSI
- **Inlet Hose:** 1/2" F NPT
- **Outlet Swivel:** 1/2" F NPT
- **Material:** Stainless Steel
- **Dimensions:** L 38.7 cm x H 31.5 cm x D 47.4 cm
- **Disc:** 45 cm
- **Weight:**
- **Brand:** BAR



Recommended Accessories

- **Handle for COX Reel (D1)** 222 2103244
- **Hose Reel - Crank - A Frame** 222 DHRA50450
- **Hose Reel Cart Kit** 222 2100465
- **Hose Reel Swivel (C1)** 222 2103246
- **Hose Reel Swivel Rep Kit (C1)** 222 2103249
- **Swivel O Ring x 1--need 2(C10)** 222 2101067
- **1/2" BSPT - Suits BAR Reel** 222 2103180

