

SKU: 125.85.402.151

Capacity: 92 m of 3/8" Hose
Perf: 5,075 PSI (Max.)
In/Out: 3/8" F NPT

Features

- Heavy Duty A-Frame Crank Reel
- A Frame style provides more support in mobile applications
- Universal 130 mm hole centre footprint
- High gloss powder-coated finish
- Extra heavy duty 6 point locking pin and adjustable rubber friction brake
- Dual heavy-duty sealed axle ball bearing with stainless steel hardware
- High-flow stainless steel swivel with Parker Viton O-Rings
- The reversible handle and swivel, let you switch sides for the best mounting option
- Hose guide to guard hose from reload damage (2100462)
- Optional 12-Volt power rewind kit. Includes mounting bracket, ring gear and hardware (103166)
- **HOSE NOT INCLUDED**

Specifications

- **Capacity:** 92 m of 3/8" Hose
- **Max Pressure:** 5,075 PSI
- **Max Flow:** 80 L/min
- **Inlet Hose:** 3/8" F NPT
- **Outlet Swivel:** 3/8" F NPT
- **Max Temperature:** 150°C
- **Material:** Stainless Steel
- **Dimensions:**
- **Weight:**
- **Brand:** BAR

Also known as JWA090



Recommended Accessories

- **1/2" BSPT - Suits BAR Reel** 222 2103180



HOSE REEL - CRANK - A FRAME

