



Technology Features - Input & Output

Input Voltage Range	240±15%
Input Frequency Range	47~63Hz
Output Voltage Range	0~rated input voltage
Output Frequency Range	0~50/60Hz
Digital Switch Input	3 input
Analogue Signal Input - AI1:	0~10V or 0~20mA input;
I2:	0~10V or 0~20mA Input
Relay Output	A pair of switched Outputs

Function Characteristics

- Sleep Function - Sleep down when there is no water consumption, to earn a better energy saving
- Freeze-Proofing Function - Suitable for low temperature area, prevent pump from freezing
- Anti-clogging Function - take precaution against pipe clogging and clean the pipe dirt
- Power On Restart - Running automatically when power on
- Day-Part Function - 3 independent day-part control, up to 7 day-part achieved when defined
- Terminal Control Mode - Terminal Run/Stop, Manual/Auto Control, Electronic Contact Gauge Control
- Various water supply Fault Alarm Functions: High-Pressure, Low-Pressure, Low-Level, Transducer Error etc.
- As many as 22 kinds of fault protection function:
- Over-Current, Over-Voltage, Low-Voltage, Over-Load etc.

The iCON iDRIVE 1220-24 is a variable speed drive to enhance the performance of single phase 240V water pumps up to 2.2 kW not exceeding 14A.

The iCON iDRIVE eliminates the requirement for large pressure tanks and pressure switches used for automatic operation as well as associated pressure cycling.

The iCON iDRIVE provides both the ability to conserve energy through only operating the pump according to the speed required to maintain constant pressure and further allowing for multiple set points to be met.

The iCON iDRIVE is equipped with an easy to use LCD display and is completely designed and built for controlling pump systems from the ground up. (IP55. Mounting bracket included.)

A Pressure Transducer 802680 4-20mA, 1mPa is required for operation.

- Professional design based on users' needs, simplicity of operation and suitable for all kinds of applications.
- According to the water condition to supply constant pressure water without manual operation after parameters are set correctly.
- Stop running automatically when there is no water consumption and Alarm automatically when faults occur.
- Adapts to many kinds of inputs.

Features:

- Constant water pressure.
- Optimises pump performance.
- Soft start, low motor start current.
- No large pressure tank required.

Protection:

- Dry run protection.
- High and low voltage protection.
- Input and output short circuit protection.
- High and low water pressure protection.
- Input and output phase failure protection.
- Over temperature protection.
- Sensor fault protection.

Conformity:

- Verification of EMC compliance certificate no. AC/0410709 to EN 61326-1:2006, EN 61000-3-2:2005, EN 61000-3-3:1995+A1:2001+A2:2005.
- Verification of LVD compliance certificate no. AC/0420709 to EN 61010-1:2001.

2 Year iCON Series Drive Warranty